



# BRASS PUSH-TO-CONNECTS

## **BRASS PUSH-TO-CONNECTS**

At Pneuline Supply, we're all about connections—fluid, precise, and oh-so-smooth. we offer Brass, Nickel-Plated Brass, and Chrome-Plated Brass Metal Push-To-Connects.



**NAC SERIES -THREADED CONNECTOR**

The nickel-plated brass fitting is user-friendly and ensures a secure lock when installed. The smooth stem facilitates easy tubing attachment. The opposite end features male threads and a fixed nut for tightening. The fitting has a working pressure of 217 psi and a temperature range of 4°F to 160°F.



**PAM SERIES - PUSH-TO-CONNECT**

The PAM Series is a push-to-connect fitting that is a compact size with a straight male hex configuration. In addition, the working pressure is 150 psi, and the temperature range is 32°F to 140°F. Nickel-plated Brass, the Buna-N O-ring, and the grip ring are Stainless Steel. Furthermore, this product is intended for use with compressed air and inert.

| SKU          | DESCRIPTION                               |
|--------------|---|
| PAM-10U14P   | 10-32 Male UNF by 1/4 OD Push-to-Connect  |
| PAM-10U14PC  | 10-32 Male UNF by 1/4 OD Push-to-Connect  |
| PAM-10U18P   | 10-32 Male UNF by 1/8 OD Push-to-Connect  |
| PAM-10U316P  | 10-32 Male UNF by 3/16 OD Push-to-Connect |
| PAM-10U532P  | 10-32 Male UNF by 5/32 OD Push-to-Connect |
| PAM-10U532PC | 10-32 Male UNF by 5/32 OD Push-to-Connect |
| PAM-1M18P    | 1/16 MNPT by 1/8 OD Push-to-Connect       |
| PAM-1M532P   | 1/16 MNPT by 5/32 OD Push-to-Connect      |
| PAM-1M14P    | 1/16 MNPT by 1/4 OD Push-to-Connect       |
| PAM-2M2P     | 1/8 MNPT by 1/8 OD Push-to-Connect        |
| PAM-2M316P   | 1/8 MNPT by 3/16 OD Push-to-Connect       |
| PAM-2M14P    | 1/8 MNPT by 1/4 OD Push-to-Connect        |
| PAM-2M4P     | 1/8 MNPT by 1/4 OD Push-to-Connect        |
| PAM-2M516P   | 1/8 MNPT by 5/16 OD Push-to-Connect       |
| PAM-2M532P   | 1/8 MNPT by 5/32 OD Push-to-Connect       |

| SKU         | DESCRIPTION                              |
|-------------|--|
| PAM-2M532PC | 1/8 MNPT by 5/32 OD Push-to-Connect      |
| PAM-2M38P   | 1/8 MNPT by 3/8 OD Push-to-Connect       |
| PAM-2M12P   | 1/8 MNPT by 1/2 OD Push-to-Connect       |
| PAM-4M18P   | 1/4 MNPT by 1/8 OD Push-to-Connect       |
| PAM-4M316P  | 1/4 MNPT by 3/16 OD Push-to-Connect      |
| PAM-4M14    | 1/4 MNPT by 1/4 OD Push-to-Connect       |
| PAM-4M532P  | 1/4 MNPT by 5/32 OD Push-to-Connect 4 MM |
| PAM-4M3P    | 1/4 MNPT by 3/16 OD Push-to-Connect      |
| PAM-4M4P    | 1/4 MNPT by 1/4 OD Push-to-Connect       |
| PAM-4M516P  | 1/4 MNPT by 5/16 OD Push-to-Connect      |
| PAM-4M38P   | 1/4 MNPT by 3/8 OD Push-to-Connect       |
| PAM-4M6P    | 1/4 MNPT by 3/8 OD Push-to-Connect       |
| PAM-4M8P    | 1/4 MNPT by 1/2 OD Push-to-Connect       |
| PAM-4R-8MMP | 1/4 R by 8 mm OD Push-to-Connect         |
| PAM-5M14P   | 5 mm by 1/4 OD Push-to-Connect           |
| PAM-6M532P  | 3/8 MNPT by 5/32 OD Push-to-Connect      |
| PAM-6M316P  | 3/8 MNPT by 3/16 OD Push-to-Connect      |
| PAM-6M3P    | 3/8 MNPT by 3/16 OD Push-to-Connect      |
| PAM-6M516   | 3/8 MNPT by 5/16 OD Push-to-Connect      |
| PAM-6M38    | 3/8 MNPT by 3/8 OD Push-to-Connect       |
| PAM-6M4P    | 3/8 MNPT by 1/4 OD Push-to-Connect       |
| PAM-6M8P    | 3/8 MNPT by 1/2 OD Push-to-Connect       |
| PAM-6M12    | 3/8 MNPT by 1/2 OD Push-to-Connect       |
| PAM-8M38    | 1/2 MNPT by 3/8 OD Push-to-Connect       |
| PAM-8M6P    | 1/2 MNPT by 3/8 OD Push-to-Connect       |
| PAM-8M8     | 1/2 MNPT by 1/2 OD Push-to-Connect       |
| PAM-8M12    | 1/2 MNPT by 1/2 OD Push-to-Connect       |
| PAM-8R-8MMP | 1/2 R by 8 MM OD Push-to-Connect         |



AC SERIES

Ac Series connectors are Brass with male or female threads on one end with a nut for tightening. The other end is smooth for ease of attaching tubing. In addition, they will connect to any 10-32 threaded inlet. The OD tube sizes are 5/32", 1/4", and 3/8".

| SKU         |                                     |
|-------------|-------------------------------------|
| AC-10F-14S  | 10-32 Female UNF by 1/4 Stem Brass  |
| AC-10F-38S  | 10-32 Female UNF by 3/8 Stem Brass  |
| AC-10F-532S | 10-32 Female UNF by 5/32 Stem Brass |
| AC-10U-14S  | 10-32 Male UNF by 1/4 Stem Brass    |
| AC-10U-38S  | 10-32 Male UNF by 3/8 Stem Brass    |
| AC-10U-532  | 10-32 Male UNF by 5/32 Stem Brass   |



SMRI SERIES

The SMRI Series Barbed Nickel-Plated Brass Quick Connect Plugs resist corrosion, have a maximum input pressure of 500 psi, a temperature range of -4° F to 210° F, and are designed to fit with the **SMRC Series** Quick Coupler bodies.

| SKU        | Description                  |
|------------|------------------------------|
| SMRI-3B    | 3/16 inch Barbed Brass Plug  |
| SMRI-532B  | 5/32 inch Barbed Brass Plug  |
| SMRI-1032F | 10-32 inch Female Brass Plug |
| SMRI-1032M | 10-32 inch Male Brass Plug   |
| SMRI-18B   | 1/8 inch Barbed Brass Plug   |