



# STAINLESS STEEL PUSH-TO-CONNECTS

**STAINLESS STEEL PUSH-TO-CONNECTS**



## TCM SERIES

TCM Series are Straight Connectors made of 316 Stainless Steel. One end is smooth for easy attachment of tubing and the other has male threads below a hex nut for tightening. Also, it has a working pressure of 290 psi and a temperature range of -4° F to 302° F. The sterilization temperature is up to 280° F. The O-Ring is Viton®. BSPT is also available.

---

| SKU            | DESCRIPTION   |
|----------------|---|
| TCM-10-532P-SS | 10-32 UNF Male by 5/32 OD 316 Stainless Steel Push-to-Connect |
| TCM-2M-14P-SS  | 1/8 MNPT by 1/4 OD 316 Stainless Steel Push-to-Connect        |
| TCM-2M-316P-SS | 1/8 MNPT by 3/16 OD 316 Stainless Steel Push-to-Connect       |
| TCM-2M-516P-SS | 1/8 MNPT by 5/16 OD 316 Stainless Steel Push-to-Connect       |
| TCM-2M-532P-SS | 1/8 MNPT by 5/32 OD 316 Stainless Steel Push-to-Connect       |
| TCM-4M-316P-SS | 1/4 MNPT by 3/16 OD 316 Stainless Steel Push-to-Connect       |
| TCM-4M-4P-SS   | 1/4 MNPT by 1/4 OD 316 Stainless Steel Push-to-Connect        |
| TCM-4M-5P-SS   | 1/4 MNPT by 5/16 OD 316 Stainless Steel Push-to-Connect       |
| TCM-4M-6P-SS   | 1/4 MNPT by 3/8 OD 316 Stainless Steel Push-to-Connect        |
| TCM-4M-8P-SS   | 1/4 MNPT by 1/2 OD 316 Stainless Steel Push-to-Connect        |
| TCM-6M-6P-SS   | 3/8 MNPT by 3/8 OD 316 Stainless Steel Push-to-Connect        |
| TCM-6M-8P-SS   | 3/8 MNPT by 1/2 OD 316 Stainless Steel Push-to-Connect        |
| TCM-8M-6P-SS   | 1/2 MNPT by 3/8 OD 316 Stainless Steel Push-to-Connect        |
| TCM-8M-8P-SS   | 1/2 MNPT by 1/2 OD 316 Stainless Steel Push-to-Connect        |